

6280 Commander[®]

HYDRAULIC WALK-BEHIND SCRAPER

6280-AUS, 6280-EUR, 6280-JPN, 6280-UK, 6280-BOL, 6280-HER, 6280-INT, 6280-KTU, 6280-SUN



The Commander removes the worst of today's soft goods, such as glued-down floors, gummy commercial carpet, VCT, sheet vinyl, rubber tile, linoleum, indoor and outdoor sport surfaces, roofing material, and more.

6280 Specifications

Power Supply	Electric	
Width	17.75"	45 cm
Max. Height	46"	117 cm
Height (handle folded)	30"	76 cm
Max. Length	51"	130 cm
Length (handle folded)	29"	74 cm
Weight	425 lb	192.8 kg
Removable Weight	47 lb front, 43 lb side	21.3 kg front, 19.5 kg side
Weight (machine only)	335 lb	152 kg
Speed	10-45 ft/min	3.0-13.7 m/min
RPM	3450/2875	
Voltage	115	230
Frequency	60 Hz	50 Hz
HP	1.5	1.12 kW
Amps (full load)	13/7.5	
Noise Emission	79 dB	

Meets the requirements of the Machine Directive 2006/42/EC and EMC Directive 2004/108/EC. It is CE marked.

SAFETY

- A.** Front-weight design better deflects loose material away from machine during use
- B.** Tie-down/lifting bail

COMFORT

- C.** Ergonomically designed, adjustable-position hand grips; hydraulic self-propelled forward and reverse; variable speed, 10 to 45 feet per minute; manual drive system for throttle/speed control and smooth transitions
- D.** Six handle positions for work under counters and other confined areas; collapses to save space during transport and storage

PERFORMANCE

- E.** Secure-mount side slide weights adjust head pressure; slide the weights back to increase weight over drive wheels
- F.** Adjustable, self-cleaning, industrial-grade, siped wheels for improved traction over smooth or slippery surfaces; clip-pin removal allows for easy nonpowered maneuvering
- G.** Motor equipped with thermal-overload-protection circuit breaker that protects against strain or electrical overload
- H.** Orbital action rotates the cutting blade to cut through a range of materials over various substrates; extends life cycle of machine while reducing maintenance costs
- I.** Transport-wheel rack hanger on back of handle
- J.** Adjustable wheel scrapers prevent material buildup during operation

INCLUDED WITH THE 6280

- 6280-299 front wheel assembly
- Kit 5173 includes:
 - 148 5" x 6" blade
 - 6258-BU 3" x 12" self-scoring blade
 - 6286 3" x 10" heavy-duty blade
 - 7050-200 3" x 6" premium high-tempered blade
 - 7050-202 3" x 10" premium high-tempered blade
- 5280-137W: 6mm T-handle wrench
- Operating and Service Manuals
- One-year manufacturer's warranty on parts and labor

RECOMMENDED ACCESSORIES

6280-505

- Swivel head rotates to allow continuous contact with the floor

6280-500

- Swivel head allows for continuous contact with the floor and is specifically for razor blades

WALK-BEHIND MACHINE ACCESSORIES



6280-505 SWIVEL HEAD ATTACHMENT

Optional swivel head attachment maintains 100 percent contact between the blade and the surface, maximizing production rates. Rotate the head 180 degrees to self-sharpen the blade during use.

- Holds blades of .062 or .094 thickness
- Works on thin, soft coatings, paint, hard-to-remove gummy or dry adhesives
- Ultimate adhesive removal
- Designed to fit on the **550**, **5280**, and **6280-COM** walk-behind machines

6280-500 SWIVEL HEAD ATTACHMENT FOR RAZOR BLADES

Optional attachment keeps your blade in contact with the surface of the floor.

- Designed to fit on the **550**, **5280**, and **6280-COM** walk-behind machines

6251 LOADING RAMP

- 15" x 6'9"

402311 REPLACEMENT WHEEL PIN

- 5/16 x 2-1/16 replacement wheel pin for the **6280** and **6280HD**

CUTTING HEADS FOR THE 6280HD GLADIATOR

- 7280-6: 6-inch cutting head
- 7280-10: 10-inch cutting head
- 7280-12: 12-inch cutting head
- 7280-14: 14-inch cutting head
- 7280-12RBH: Razor blade head

7280-12RBH

- Razor blade head for **6280HD-COM**



7280-2B ANGLE ATTACHMENT

- 22-degree angle attachment for soft goods removal with the **6280HD**

7280-2C ANGLE ATTACHMENT

- 30-degree angle attachment for hard goods removal with the **6280HD**



402276

- 9 degree angle attachment

7280-4 RETAINER CAP ASSEMBLY

- Replacement assembly for **6280HD** shanks

Blades and Shanks

The industry's largest selection of scraper blades, including our patented line, is always in stock and available. Our patented carbide blades are engineered for the toughest ceramic and hardwood removal applications and are gaged at a specific Rockwell hardness for maximum efficiency and longevity.



ELECTRIC POWER



BATTERY POWER



PROPANE